

## RXE020-2 Product Details



**RXE020-2**

TE Internal Number: 840195-000

**Obsolete**

[Contact Product Information Center](#)

### PolySwitch Resettable Devices

[Always ELV Compliant](#) ([Find RoHS Compliant Alternates/Statement of Compliance](#))

#### Product Highlights:

- Radial Application
- Family Name = RXE
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = .2 Amps.
- IT (Room Temperature) = .40 Amps.

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

### Documentation & Additional Information

<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RXE020</a> (PDF, English)</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>
--	--

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• UL Recognized = File No. E74889</li> <li>• CSA File No. = 78165C</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">IH (Room Temperature) (Amps.)</a> = 0.2</li> <li>• <a href="#">IT (Room Temperature) (Amps.)</a> = 0.40</li> <li>• <a href="#">Vmax Operating (V)</a> = 72</li> <li>• <a href="#">Rmin (?)</a> = 1.83</li> <li>• <a href="#">Rmax (?)</a> = 2.750</li> <li>• <a href="#">R1 Max [Post Trip] (?)</a> = 4.40</li> <li>• Power Dissipation (Typical) (W) = 0.41</li> </ul> <p><b>Termination Related Features:</b></p> <ul style="list-style-type: none"> <li>• Construction = Radial, Through Hole</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• Lead Type = Standard Kinked Lead</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Family Name</a> = RXE</li> </ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• Coating = Coated</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = ELV compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>• RoHS/ELV Compliance History = Always was ELV compliant</li> <li>• TUV Certificate No. = R72041428</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Operating Temperature (Max.) (°C)</a> = 85</li> </ul> <p><b>Operation/Application:</b></p> <ul style="list-style-type: none"> <li>• Application = Radial</li> </ul> <p><b>Packaging Related Features:</b></p> <ul style="list-style-type: none"> <li>• Packaging Method = Tape &amp; Reel</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Raychem</li> </ul>
--	---