

419D

ACRYLIC CONFORMAL COATING

Safety Data Sheet

Section 1: Identification


Product Identifier and Other Means of Identification

Product Identifier: 419D**Other Means of Identification:** Acrylic Conformal Coating**Related Part #** 419D-55ML, 419D-1L, 419D-4L, 419D-20L, 419D-200L

Recommended Use and Restriction on Use

Use: Protective coating for printed circuit boards**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA +1-800-340-0772**Fax** +1-800-340-0773**E-mail** support@mgchemicals.com**Web** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

419D

ACRYLIC CONFORMAL COATING

Section 2: Hazard(s) Identification



Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Irritation	Eye	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

Section continued on the next page

419D
ACRYLIC CONFORMAL COATING
Continued...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No Smoking.
P233	Keep container tightly closed.
P261, P271	Avoid breathing mist, vapors, and spray. Use only outdoors or in a well-ventilated area.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P243	Take action to prevent static discharges.
P280	Wear protective gloves, protective clothing, and eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Section continued on the next page

419D
ACRYLIC CONFORMAL COATING
Other Hazards

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	% (weight)
123-86-4	n-butyl acetate	55%
78-93-3	butan-2-one ^{a)}	15%
80-62-6	methyl methacrylate	<0.1%
97-88-1	n-butyl methacrylate	<0.1%

a) Also known as methyl ethyl ketone (MEK)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN (or hair)	P303 + P361 + P353
Immediate Symptoms	<i>redness, rash, dry skin</i>
Response	Take off immediately all contaminated clothing. Rinse skin with water.
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>dizziness, drowsiness, cough, headaches, sore throat, nausea</i>
Response	Remove person to fresh air and keep comfortable for breathing. If you feel unwell: Call a doctor.

Section continued on the next page

419D

ACRYLIC CONFORMAL COATING

Continued...

IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>nausea, sore throat, diarrhea, drowsiness, dizziness, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	The liquid may float on water and ignite. The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂)
Fire-Fighter	Wear self-contained breathing apparatus and full fire fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist, spray, and vapors. Remove or keep away all sources of ignition or extreme heat.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and nonflammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

419D

ACRYLIC CONFORMAL COATING

Section 7: Handling and Storage

Prevention

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Take precautionary measures against static discharge.

Keep container tightly closed.

Avoid breathing mist, vapors, and spray. Use only outdoors or in a well-ventilated area.

Handling

Wear protective gloves, protective clothing, and eye protection.

Wash hands thoroughly after handling.

Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

419D
ACRYLIC CONFORMAL COATING
Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
n-butyl acetate	ACGIH	50 ppm	150ppm
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	200 ppm
	Canada BC	20 ppm	Not established
	Canada ON	150 ppm	200 ppm
	Canada QC	150 ppm	200 ppm
butan-2-one	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	200 ppm	Not established
	Canada AB	200 ppm	300 ppm
	Canada BC	50 ppm	100 ppm
	Canada ON	200 ppm	300 ppm
	Canada QC	150 ppm	300 ppm
methyl methacrylate	ACGIH	50 ppm ^{a)}	100 ppm
	U.S.A. OSHA PEL	100 ppm	Not established
	Canada AB	50 ppm	100 ppm
	Canada BC	Not established	Not established
	Canada ON	50 ppm	100 ppm
	Canada QC	100 ppm	Not established
n-butyl methacrylate	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	Not established	Not established
	Canada BC	50 ppm	Not established
	Canada ON	Not established	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long-term permissible exposure limits (PEL) for 8 h.

Engineering Controls
Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

Section continued on the next page

419D

ACRYLIC CONFORMAL COATING**Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

419D
ACRYLIC CONFORMAL COATING
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit ^{c)}	1.6%
Appearance	Clear	Upper Flammability Limit ^{c)}	10.4%
Odor	Fruity	Vapor Pressure @20 °C ^{c)}	11 hPa [8.3 mmHg]
Odor Threshold	0.007 ppm	Vapor Density	>2.5 (Air =1)
pH	Not available	Relative Density @25 °C	0.94
Freezing/Melting Point	Not available	Solubility in Water	Slightly soluble
Initial Boiling Point ^{a)}	≥80 °C [≥176 °F]	Partition Coefficient (n-octanol/water)	Not available
Flash Point ^{b)}	-9 °C [16 °F]	Auto-ignition Temperature ^{d)}	≥400 °C [≥752 °F]
Evaporation Rate	<1 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Highly flammable	Viscosity @25 °C	110 mm ² /s

a) Values based on butan-2-one component.

b) Pensky-Martens closed cup

c) Calculated based on components.

d) Values based on n-butyl methacrylate, which is the component with the lowest auto-ignition value.

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Ignition sources, open flames, and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

419D
ACRYLIC CONFORMAL COATING
Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	May cause redness, severe irritation, or pain.
Skin	May cause skin redness, pain, and dry skin.
Inhalation	May cause dizziness, drowsiness, cough, headaches, sore throat or nausea.
Ingestion	May cause nausea, sore throat, diarrhea, or vomiting (see inhalation symptoms).
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	>21 mg/L 4 h Rat
butan-2-one	2 737 mg/kg Rat	6 480 mg/kg Rabbit	23 500 mg/m ³ 8 h Rat
methyl methacrylate	7 872 mg/kg Rat	>5 000 mg/kg Rabbit	78 mg/L 4 h Rat
n-butyl methacrylate	≥2 000 mg/kg Rat	>2 000 mg/kg Rabbit	29.8 mg/L 4 h Rat
Mixture ATE	>5 000 mg/kg	>5 000 mg/kg	221 mg/L

Note: Toxicity data from the ECHA database were consulted. The data from supplier SDSs were also consulted.

Section continued on the next page

419D

ACRYLIC CONFORMAL COATING**Other Toxicological Effects**

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Butan-2-one is a known serious eye irritant.
Sensitization (allergic reactions)	The n-butyl methacrylate and methyl methacrylate may cause skin sensitization according to animal studies.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	The n-butyl acetate, butan-2-one, and 1-methoxy-2-propanol acetate components can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There are no cat 1 substances, and the kinematic viscosity is $>20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The n-butyl acetate ingredient is an acute category 3 environmental toxicant (biodegradable, with minimal LC50 of 18 mg/L for fathead minnow).

The 2-butanone (MEK) ingredient is not classified as an environmental hazard according to GHS criteria.

Section continued on the next page

419D**ACRYLIC CONFORMAL COATING****Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Expected to be biodegradable. The volatile solvent constituents will oxidize rapidly in air by photochemical reaction.

Other Effects

Regulated Volatile Organic Compounds (VOC) content according to the US (EPA) and Canadian (CEPA) authorities.

VOC = 70% [658 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

419D

ACRYLIC CONFORMAL COATING

Section 14: Transport Information

Ground

Refer to TDG (Canadian Transportation of Dangerous Goods regulations) and **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 5 L and under

419D-55ML, 419D-1L, 419D-4L

Limited Quantity



Sizes greater than 5 L

419D-20L, 419D-200L

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: No



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 0.5 L and under

419D-55ML

Limited Quantity



Max Net QTY/Pkg
1 L gross

Sizes up to 5 L (passenger) or 60 L (cargo)

419D-1L, 419D-4L, 419D-20L, 419D-200L

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: No



Sea

Refer to IMDG regulations.

Sizes 5 L and under

419D-55ML, 419D-1L, 419D-4L

Limited Quantity



Sizes greater than 5 L

419D-20L, 419D-200L

UN number: UN1263

Shipping Name: PAINT

Class: 3

Packing Group: II

Marine Pollutant: No



Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

419D
ACRYLIC CONFORMAL COATING
Section 15: Regulatory Information
Canada
Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)


All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA
Other Classifications
HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES


Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains methyl methacrylate, which is listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains methyl methacrylate (CAS# 80-62-6; reportable quantity = 1 000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains n-butyl acetate (CAS# 123-86-4) and 2-butanone (CAS# 78-93-3), which are subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

Section continued on the next page

419D**ACRYLIC CONFORMAL COATING****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances known to be listed in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronic equipment and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by	Regulatory Department
Date of Revision	05 December 2022
Supersedes	26 February 2020
Reason for Changes:	Change to regulatory information

Reference

1) ACGIH 2022 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2022).

Section continued on the next page

419D**ACRYLIC CONFORMAL COATING****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
Wt	Weight

Technical Queries

Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses

Manufacturing & Support
1210 Corporate Drive
Burlington, Ontario
Canada
L7L 5R6

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.