





Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 402E

Other Means of Identification: Electronic Super Duster / Super Duster Électronique

Related Part # 402E

Recommended Use and Restriction on Use

Use: Duster for electronics maintenance **Uses Advised Against:** Not available

Details of Manufacturer or Importer

Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones



Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Based on available data, this product does not meet the HCS 2012 or WHMIS 2015 classification criteria.

The product is classified as an article and is exempted from GHS classification, but information is provided herein in good faith, for information only.

Under normal conditions of use, the lithium-ion battery is embedded in the device; therefore, it doesn't present immediate physical or health hazards. But if the battery is damaged, opened, or burned, it can lead to physical hazards, such as fire, as well as to health hazards due to hazardous chemicals exposure via inhalation, skin contact, eye contact, and ingestion.

Label Elements

Signal Word	No signal word
Pictograms	Hazard Statements
None mandated	None

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None



Section 3: Composition/Information on Ingredients

Chemical Name	%(weight)
lithium cobalt oxide	15-40%
graphite	10-30%
lithium hexafluorophosphate	10-30%
copper	7-13%
aluminum	5-10%
nickel	1-5%
	lithium cobalt oxide graphite lithium hexafluorophosphate copper aluminum

Section 4: First-Aid Measures

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF IN EYES	P305 + P351 + P338
Immediate Symptoms	Low toxicity: redness, mild irritation
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN	P302 + P352
Immediate Symptoms	Low toxicity: mild irritation
Response	Wash with plenty of water.
IF INHALED	P304 + P340
Immediate Symptoms	Low toxicity
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	Low toxicity
Response	Rinse mouth. Do NOT induce vomiting.







Section 5: Fire-Fighting Measures

Chemica

Extinguishing Media Use extinguishing media suitable for surrounding materials.

For battery fire, use metal fire extinguishing powder or dry

sand. Avoid water extinguishing media.

Specific Hazards Not flammable or combustible but burns if involved in a fire.

Combustion Products Produces carbon oxides (CO, CO₂) and lithium oxides (Li₂O),

cobalt oxides.

Fire-Fighter Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

Section 6: Accidental Release Measures

Personal Protection See personal protection recommendations in Section 8.

For damaged batteries, wear chemically resistant gloves and

safety glasses.

Precautions for

Response

Clean spilled surfaces with soap and water and collect waste in

an electronic waste container.

Environmental

Precautions

Avoid releasing to the environment.

Containment Methods Not applicable

Cleaning Methods Collect waste in a container for electronic waste. Use soap and

water to remove the last traces of residue.

Disposal Methods Dispose of electronic waste at an official e-waste drop-off point.



SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Section 7: Handling and Storage

Prevention Keep out of reach of children.

Do not open, take apart, crush or burn the battery cell.

Do not allow terminals to short circuit.

Do not expose to high heat or fires. Avoid direct sunlight.

Avoid eye or skin contact.

Handling Wear eye protection.

Storage For long term storage, keep between -10 °C to 35 °C.

SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
Lithium cobalt oxide	ACGIH	0.02 mg/m ³	Not established
(Cobalt and inorganic	U.S.A. OSHA	0.1 mg/m ³	Not established
compounds as cobalt)	Canada AB	0.02 mg/m ³	Not established
	Canada BC	0.02 mg/m ³	Not established
	Canada ON	0.02 mg/m ³	Not established
(fumes or dust)	Canada QC	0.05 mg/m^3	Not established
Graphite	ACGIH	2 mg/m ³	Not established
	U.S.A. OSHA	15 mppcf	Not established
	Canada AB	2 mg/m ³	Not established
	Canada BC	Not established	Not established
	Canada ON	2 mg/m ³	Not established
	Canada QC	2.5 mg/m ³	Not established
Copper	ACGIH	1 mg/m ³	Not established
	U.S.A. OSHA	Not established	Not established
	Canada AB	1 mg/m ³	Not established
	Canada BC	Not established	Not established
(dust)	Canada ON	1 mg/m ³	Not established
	Canada QC	Not established	2 mg/m ³
Aluminum	ACGIH	1 mg/m ³	Not established
(metal and insoluble	U.S.A OSHA	15 mg/m ³	Not established
compounds)	Canada AB	2 mg/m ³	Not established
	Canada BC	Not established	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	Not established	Not established
Nickel	ACGIH	1.50 mg/m ³	Not established
	U.S.A OSHA	1 mg/m ³	Not established
	Canada AB	1.50 mg/m ³	Not established
	Canada BC	0.05 mg/m^3	Not established
	Canada ON	1 mg/m ³	Not established
	Canada QC	1 mg/m ³	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the suppliers' SDSs were also consulted. Short term exposure limits (STEL) are usually for 15 min and long-term permissible exposure limits (PEL) for 8 h.

mppcf = Million of particles per cubic foot of air, based on impinge samples counted by light-field technique.

Section continued on the next page

Page **6** of **16**



SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Engineering Controls

Ventilation Normal ventilation is generally adequate, except in enclosed or

low-lying area.

Since the battery compounds are sealed in the device and battery pack, it is not available as a respiration hazard under

normal conditions.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses.

RECOMMENDATION: Ensure that glasses have side shields for

lateral protection.

Skin Protection For likely contacts with damaged cell content, use of protective

nitrile gloves or other chemically resistant gloves.

Respiratory Protection Under normal conditions of uses, no respiratory protection

should be required due the low exposure to fume and vapors.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3.

The respirator should be fitted to the employee by a

professional.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Section 9: Physical and Chemical Properties

Physical State Solid **Lower Flammability** Not Limit applicable **Appearance** Article **Upper Flammability** Not Limit applicable Odor Odorless **Vapor Pressure** Not @20 °C available **Odor Threshold** Not **Vapor Density** Not available applicable Not **Relative Density** Not pН applicable @25 °C applicable Insoluble Freezing/Melting Not Solubility in **Point** available Water **Partition Coefficient Initial Boiling** Not Not **Point** n-octanol/water available available **Flash Point** Not **Auto-ignition** Not available **Temperature** available **Evaporation** Not **Decomposition** 90 °C Rate available **Temperature** [194 °F] **Flammability** Non **Viscosity** Not @40°C applicable available

Section 10: Stability and Reactivity

Reactivity Not available

Chemical Chemically stable at normal temperatures and pressures **Stability**

Conditions to Do not heat above 70°C. Avoid exposing material to humid

conditions over a long period of time.

Do not deform, disassemble, or crush.

Incompatibilities Strong oxidizing agents, strong acids

Polymerization Will not occur

Avoid

Decomposition May produce toxic fumes and may form peroxides.





Section 11: Toxicological Information

Summary of Effects and Symptoms by Routes of Exposure

Eyes Low Toxicity under normal conditions. Skin Low Toxicity under normal conditions. Inhalation Low Toxicity under normal conditions. Ingestion Low Toxicity under normal conditions.

Chronic Low Toxicity—No known long-term effects.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
lithium cobalt oxide	>5 000 mg/kg	>2 000 mg/kg	5.05 mg/L
	Rat	Rat	Rat 4 h (dust)
graphite	>2 000 mg/kg	Not	2 mg/L
	Rat	available	Rat 4 h
lithium hexafluorophosphate	≥50 mg/kg	Waived-	Waived-
	Rat	corrosive	corrosive
copper	>2 500 mg/kg	>2 000 mg/kg	5.11 mg/L
	Rat	Rat	Rat 4 h (dust)
aluminum	>2 000 mg/kg	Not	Not
	Rat	available	available
nickel	>5 000 mg/kg	Not	10.20 mg/L
	Rat	available	Rat 1 h (dust)

Note: Toxicity data from the ECHA database were consulted. The data from supplier SDSs were also consulted.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Other Toxicological Effects

Skin corrosion/irritation If cell ruptured, lithium hexafluorophosphate(1-) is a

category 1A skin corrosive substance.

Serious eye

damage/irritation

If cell ruptured, lithium hexafluorophosphate(1-) is a category 1 eye damaging substance.

Sensitization Based on available data, the classification criteria are

(allergic reactions) not met.

Carcinogenicity Cobalt lithium dioxide [12190-79-3]

(risk of cancer) IARC Group 2B: Possibly carcinogenic to humans

ACGIH A3: Confirmed Animal Carcinogen with

Unknown Relevance to Humans CA Prop 65: Listed as a carcinogen

NTP: Reasonably anticipated to be human carcinogen

Mutagenicity Based on available data, the classification criteria are

not met. (risk of heritable genetic effects)

Reproductive Toxicity If cell ruptured, cobalt lithium dioxide is a category 1B

reproductive toxicant. (risk to sex functions)

Teratogenicity Based on available data, the classification criteria are

not met. (risk of fetus malformation)

STOT-single exposure If cell ruptured, fumes and vapors may be respiratory

irritants.

STOT-repeated exposure If cell ruptured, lithium hexafluorophosphate(1-) is a

> category 1 STOT-RE toxicant that damages bones and teeth. Ethylene carbonate is a category 2 STOT-RE

toxicant that damages kidneys.

Aspiration hazard Not applicable. There are no category 1 components,

and the kinematic viscosity is $> 20.5 \text{ mm}^2/\text{s}$.

Page 10 of 16

SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (http://echa.europa.eu), and other reliable sources.

Cobalt lithium dioxide is a category 1, M = 10, chronic aquatic toxicant.

Acute Ecotoxicity

Based on available data, the classification criteria are not met.

Chronic Ecotoxicity

Based on available data, the classification criteria are not met.

Biodegradability

Not available

Bioaccumulation

Not available

Other Effects

Not available





SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations. Dispose of electronic waste at an official e-waste drop-off point.

Section 14: Transport Information

402E Electronic Air Blower specifications

Battery Capacity: 2000 mAh

Battery Voltage: 11.1 V

Watt-hour Rating: 22.2 Wh

Battery weight: 137 g Unit gross weight: 362 g

The lithium-ion battery in the air duster blower

- Meets test requirement of subsection 38.3 of Part III of the Manual of Tests and Criteria.
- Affords protection against damage and short circuit, including protection against contact with conductive materials within the same packaging that could lead to a short circuit.

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); USA DOT 49 CFR (Parts 100 to 185) Regulations.		
	Sizes up to 5 kg (passenger)	
	402E	
LTD QTY Forbidden	UN Number: UN3481	
	Shipping name: LITHIUM ION BATTERIES	
	CONTAINED IN EQUIPMENT	
	Class: 9	
	Packing group: N/A	
	Marine pollutant: No	
TDC Small hattory overn	tion applies as not requirements of special provision 24	

TDG Small battery exemption applies as per requirements of special provision 34.

DOT Small battery exemption applies as per requirements of §173.185(c) and special provision 181.

INSTRUCTION: Ensure that the regulatory requirements are met. When shipping, declare the presence of the lithium ion battery in the device to postal carriers, couriers or transport companies.

Section continued on the next page

Page **12** of **16**

SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Air

Refer to ICAO-IATA Dangerous	s Goods Regulations.
------------------------------	----------------------

Maximum of 5 kg (passenger) or 35 kg (cargo)

402E

LTD QTY Forbidden UN Number: UN3481

Shipping name: LITHIUM ION BATTERIES

CONTAINED IN EQUIPMENT

Class: 9

Packing group: N/A **Marine pollutant:** No

It is forbidden to transport by aircraft any batteries that are damaged, defective, recalled, or recycled.

Sea

Refer to IMDG regulations.	
	Sizes up to 5 kg (passenger carrying) 402E
LTD QTY Forbidden	UN Number: UN3481
	Shipping name: LITHIUM ION BATTERIES
	CONTAINED IN EQUIPMENT
	Class: 9
	Packing group: II
	Marine pollutant: No
IMDG See requirements of	f special provision 188.



Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA

Other Classifications

HMIS® RATING

HEALTH:	*	1
FLAMMABILITY:		0
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		·

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains does not contain substances which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are listed on the TSCA active list.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any of the listed substances.

Section continued on the next page

Page **14** of **16**



SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is an electronics equipment and is therefore governed by this regulation.

Section 16: Other Information

SDS Prepared by Regulatory Department

Date of Review 08 June 2023 Supersedes 16 March 2023

Reason for Changes: Update to section 3, 8, and 11.

Reference

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
	Section continued on the next page

Page **15** of **16**



SAI Global File #004008 Burlington, Ontario, Canada

402E ELECTRONIC SUPER DUSTER

Technical Queries Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*

1210 Corporate Drive

Burlington, Ontario, Canada

L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only.

M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional,

national, and international regulations.